

RSFR-135G(3X)

High shrink ratio,flexible heat shrink tubing

Features

- 1.Flexible
- 2.High shrink ratio
- 3.Flame retardant
- 4.Resistant to common fluids and solvents
- 5.Continuous Operating Temperature:-55°C to 135°C
- 6.Shrink Temperature:120°C
- 7.RoHS compliant
- 8.Meet SAE-AMS-DTL-23053/5



Dimensions

Size		As supplied	After Recovery(mm)		Standard Package
Inch	mm	Internal diameter Minr(mm)	Internal diameter(mm)	Wall thickness(mm)	Spool Length m/spool
1/16	1.5	1.5	0.5	0.45	200
1/8	3	3.0	1.0	0.55	200
3/16	4.5	4.5	1.0	0.60	100
1/4	6	6.0	2.0	0.65	100
3/8	9	9.0	3.0	0.75	50
1/2	12	12.0	4.0	0.75	50
5/8	15.0	15.0	5.0	0.80	50
3/4	18.0	18.0	6.0	0.85	50
1	24.0	24.0	8.0	1.00	25
1-1/4	30.0	30.0	10.0	1.15	1.22
1-1/2	39.0	39.0	13.0	1.50	1.22
	50	50	16	2.50	1

2					
	60	60	20	2.60	1
	70	70	23	2.60	1
3	80	80	26	2.60	1
	90	90	30	2.60	1
4	100	100	33	2.60	1

Technical Data Physical

Property	Test Method	Typical Performance
Tensile Strength	ASTM D2671	10.4MPa
Elongation(%)	ASTM D2671	200%

Electrical

Property	Test Method	Typical Performance
Dielectric Strength	IEC 243	$\geq 15\text{kv/mm}$
Volume Resistivity	IEC 93	$\geq 1 \times 10^{14} \Omega \cdot \text{cm}$

Shenzhen Woer Heat-Shrinkable Material Co.,Ltd.

Website: <http://en.woer.com> E-mail: woer@woer.cn woer@woer.com Fax: +86 755 28299160