

WMPG

Heat Shrinkable Busbar Insulating Tube

Voltage Class:1kv,10kv,35kv.

Available colors:Red,Yellow,Green,Black.

Features:

- 1.Avoid short circuit fault caused by small animals such as mice,snakes and so on.
- 2.Prevent busbar from chemical corrosion effected by strong acid,alkali,salt etc
- 3.Avoid accidental injury to overhaul persons when they enter electriferous clearance bu mistakes.
- 4.It provides excellent insulation performance to supply required flashover protection for the busbar system.



Dimensions

Part NO	Busbar Width (mm)	As Supplied(mm)		After Recovery(mm)		Standard Package(m/roll)
		Inner Diameter	Wall thickness	Max.Inner Diameter	Wall thickness	
1kv WMPG 30	30	31.5±1.0	0.45±0.15	15	0.95±0.15	50
1kv WMPG 35	40	37.5±1.5	0.50±0.15	16	1.0±0.15	50
1kv WMPG 40	40	40.5±1.5	0.50±0.15	20	1.0±0.15	50
1kv WMPG 50	50	50.5±2.0	0.50±0.15	25	1.0±0.15	25
1kv WMPG 60	60	60±3.0	0.80±0.2	30	1.3±0.2	25
1kv WMPG 70	80	70±3.0	0.8±0.2	32	1.5±0.3	25
1kv WMPG 80	80/100	80±3.0	0.8±0.3	40	1.5±0.3	25
1kv WMPG 90	100	90±4.0	0.8±0.3	43	1.5±0.3	25
1kv WMPG 100	100/120	100±4.0	0.8±0.3	50	1.5±0.3	25
1kv WMPG 120	150	120±4.0	0.8±0.3	60	1.5±0.3	25
1kv WMPG 150	180	150±4.0	0.8±0.3	75	1.5±0.3	25

10KV

Part NO	Busbar Width (mm)	As Supplied(mm)		After Recovery(mm)		Standard Package(m/roll)
		Inner Diameter	Wall thickness	Max.Inner Diameter	Wall thickness	

10kv WMPG 20	20	20±0.8	1.0±0.2	9	2.5±0.2	25
1kv WMPG 30	30	30±0.8	1.0±0.2	13	2.5±0.2	25
10kv WMPG 40	40	40±1.0	1.2±0.2	15	2.5±0.2	25
10kv WMPG 50	50	50±2.0	1.2±0.2	20	2.5±0.2	25
10kv WMPG 60/65	60	65±3.0	1.2±0.2	24	2.5±0.2	25
10kv WMPG 80	80/100	80±3.0	1.2±0.3	32	2.8±0.3	25
10kv WMPG 100	100/120	100±4.0	1.2±0.3	40	2.8±0.3	25
10kv WMPG 120	150	120±4.0	1.2±0.3	48	2.8±0.3	25
10kv WMPG 150	200	150±4.0	1.2±0.3	60	2.8±0.3	25
10kv WMPG 180	Max	180±5.0	1.2±0.3	70	2.8±0.3	25
10kv WMPG 210	Max	210±5.0	1.2±0.3	80	2.8±0.3	20

35KV

Part NO	Busbar Width (mm)	As Supplied(mm)		After Recovery(mm)		Standard Package(m/roll)
		Inner Diameter	Wall thickness	Max.Inner Diameter	Wall thickness	
35kv WMPG 30	30	30±1.0	2.0±0.3	13	4.0±0.3	15
35kv WMPG 40	40	40±1.0	2.0±0.3	15	4.0±0.3	15
35kv WMPG 50	50	50±2.0	2.2±0.3	20	4.5±0.3	15
35kv WMPG 60/65	60	65±2.0	2.2±0.3	24	4.5±0.3	15
35kv WMPG 80	80/100	80±3.0	2.2±0.3	32	4.5±0.3	15
35kv WMPG 100	100/120	100±4.0	2.5±0.3	40	4.5±0.3	15
35kv WMPG 120	150	120±4.0	2.5±0.3	48	5.0±0.3	15
35kv WMPG 150	200	150±4.0	2.5±0.3	60	5.0±0.3	15
35kv WMPG 180	Max	180±5.0	2.5±0.3	70	5.5±0.3	15
35kv WMPG 210	Max	210±5.0	2.5±0.3	80	5.5±0.3	15

Shenzhen Woer Heat-Shrinkable Material Co.,Ltd.

Website: <http://en.woer.com> E-mail: woer@woer.cn woer@woer.com Fax: +86 755 28299160